

LIGHT CARS & TRUCKS

Service Pro[®] All Makes All Models Antifreeze/Coolant



Yellow

Ethylene Glycol

Good

No

No

OAT
Technology

Up to 5 Years/
150,000 Miles



Service Pro[®] Low Silicate Antifreeze/Coolant



Green

Ethylene Glycol

Good

No

Low Silicate

Formulated
for older
Vehicles

Up to 2 Years/
50,000 Miles

1994 & Older

2001 & Older

2002 & Older

1989 & Older

1989 & Older

Service Pro[®] Dex-Cool Compatible Antifreeze/Coolant



Orange

Ethylene Glycol

Good

No

No

Dex-Cool Compatible
for GM Vehicles

Up to 5 Years/
150,000 Miles



Antifreeze Color

Base

Delivers Longer
Engine Life

Nitrites

Silicates

Chemistry

Service Intervals**

General Motors

Chrysler

Ford

Asian Vehicles

European Vehicles



Top Off:

- ✓ Enhance system performance
- ✓ Fill overflow tank to max level to rejuvenate your existing antifreeze
- ✓ Requires 1 Gallon of 50/50



Drain and Fill:

- ✓ Refresh system to help stop the spread of corrosion and protect against freeze-up and boil-over
- ✓ With cool engine, open drain valve to empty and refill to indicated level
- ✓ Requires 2 Gallons of 50/50



Flush and Fill:

- ✓ Completely rejuvenate entire cooling system, stopping corrosion and providing ultimate freeze-up and boil-over protection
- ✓ Flush according to directions. Add half the volume of the cooling system with Concentrate. Top off with distilled water until full.
- ✓ Requires 1-2 Gallons of Concentrate Antifreeze

All products available in concentrate and 50/50

HEAVY DUTY VEHICLES

	Purus® Heavy Duty Nitrite-Free Ext. Life Antifreeze/Coolant	Purus® Heavy Duty Ext. Life Antifreeze/Coolant	Purus® Heavy Duty SCA Pre-Charged Antifreeze/Coolant
Antifreeze Color	Yellow	Red	Purple
Base	Ethylene Glycol	Ethylene Glycol	Ethylene Glycol
Delivers Longer Engine Life	Best	Better	Good
Nitrites	No	Yes	Yes
Silicates	No	No	Low Silicate
Chemistry	Nitrite Free OAT Technology	Extended Life NOAT Technology	Extended Service Interval Technology
Service Intervals**	Up to 600,000 Miles/12,000 hours service life**	Up to 600,000 Miles/12,000 hours service life**	Follow OE or TMC Recommendation for PM Services
General Motors	✓* HD	✓* HD	✓* HD
Chrysler	✓* HD	✓* HD	✓* HD
Ford	✓* HD	✓* HD	✓* HD
Asian Vehicles	✓* HD	✓* HD	✓* HD
European Vehicles	✓* HD	✓* HD	✓* HD
Farm/Off-Road	✓* HD	✓* HD	✓* HD



Top Off:

- ✓ Enhance system performance
- ✓ Fill overflow tank to max level to rejuvenate your existing antifreeze
- ✓ Requires 1 Gallon of 50/50



Drain and Fill:

- ✓ Refresh system to help stop the spread of corrosion and protect against freeze-up and boil-over
- ✓ With cool engine, open drain valve to empty and refill to indicated level
- ✓ Requires 2 Gallons of 50/50



Flush and Fill:

- ✓ Completely rejuvenate entire cooling system, stopping corrosion and providing ultimate freeze-up and boil-over protection
- ✓ Flush according to directions. Add half the volume of the cooling system with Concentrate. Top off with distilled water until full.
- ✓ Requires 1-2 Gallons of Concentrate Antifreeze

All products available in concentrate and 50/50

THIS IS STRICTLY A GUIDE - * Heavy Duty applications include diesel-powered commercial vehicles or stationary engines with aluminum or other engine metals. **Always consult your vehicle manufacturer's owner's manual to determine the specific maintenance and change-over intervals recommended for your vehicle. UNDER THE MAGNUSON WARRANTY IMPROVEMENT ACT - A manufacturer may not condition a warranty on using a specific product identified by brand, unless the product is provided to the consumer free of charge, or by special waiver from the Federal Trade Commission after the manufacturer has proved that the vehicle engine will not function properly without the use of the specified brand or product.